

MATERIAL SAFETY DATA SHEET (SUBSTITUTES FOR OSHA FORM 174): May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200.

PRODUCT NUMBER: 541  
IDENTITY: COIL POWER 20A Revision Date: 08/09/2004

Section I

Manufacturer's Name: NATIONAL AMERICAN SALES \* Telephone Numbers:  
Address: P.O. BOX 68 Emergency:  
800/255-3924  
THIBODAUX Information:  
State: LA Zip Code: 70302 985/447-1434

HMS CODES: REACTIVITY: 1 FLAMMABILITY: 0 HEALTH: 3 PERSONAL PROTECT: B

Section II: HAZARDOUS INGREDIENTS/IDENTITY INFORMATION (All of the ingredients contained in this product are listed on the TSCA inventory.)

Name	Cas No.	OSHA PEL	ACGIH TLV	OTHER LIM	%
POTASSIUM HYDROXIDE	1310-58-3	N/A	2 MG/M3	N/A	---
PROPANE/N-BUTANE	68476-86-8	1000 PPM	600 PPM	N/A	---
SODIUM HYDROXIDE *	1310-73-2	2 MG/M3	2 MG/M3	N/A	---

Comment:  
THIS PRODUCT CONTAINS THE TOXIC CHEMICALS MARKED WITH AN \* SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF THE EMERGENCY PLANNING AND COMMUNITY RIGHT-TO-KNOW ACT OF 1986 AND OF 40CFR372.

Section III: PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point: 212F Specific Gravity (water=1) 1.05  
Vapor Pressure (mm Hg) <20 Melting Point: N/A  
Vapor Density (AIR=1) 1 Evaporation Rate: <1  
Solubility in Water: 100% (Butyl Acetate=1)  
Appearance and Odor: WHITE FOAM

Section IV: FIRE AND EXPLOSION HAZARD DATA

Flash Point (Method Used): NONE Flammable Limits: LEL: N/A UEL: N/A  
Extinguishing Media: WATER, STANDARD DRY CHEMICAL FIRE EXTINGUISHER.  
Special Fire Fighting Procedures: SELF CONTAINED BREATHING APPARATUS.

Unusual Fire and Explosion Hazards: CONTENTS UNDER PRESSURE. EXPOSURE TO TEMPERATURES ABOVE 120 F MAY CAUSE BURSTING.

Section V: REACTIVITY DATA

PRODUCT NUMBER: 541

Stability: Unstable: Conditions to avoid:  
Stable: X NONE  
Incompatibility (Materials to Avoid): STRONG OXIDIZERS, ALKALIES, ACIDS