

(MSDS)

ITEM NUMBER: 841 - STAINLESS STEEL CLEANER 15 OZ.  
 VERSION 4 EFFECTIVE DATE: 07/31/02 SUPERCEDES: 06/15/02 ORIGINALLY PREPARED BY: Sue Heiser

Section(s) Revised: IX

IDENTITY (As Used On Label and List): STAINLESS STEEL CLEANER 15 OZ. **SHINEY**

EMERGENCY MEDICAL Telephone# 1-800-228-5635 X 009 (24 Hrs) Outside of the U.S.A. Call 651-632-9275

PRODUCT HAZARD RATINGS (HMIS): Health = 2, Fire = 4, Reactivity = 0, Protective Equipment = B  
 (Rating Legend: - 4 = Extreme, 3 = Serious, 2 = Moderate, 1 = Slight, 0 = Minimal, \* = Chronic Hazard)

SECTION I  
**NATIONAL AMERICAN SALES CORP** TELEPHONE NUMBER FOR INFORMATION: 630-543-7600 **800-821-3732**  
**P.O. BOX 68**  
**THIBODAUX, LA 70302** DATE PRINTED: 7/06/04 NAME OF PREPARER: REGULATORY COMPLIANCE

IL 60101

SECTION II - HAZARDOUS INGREDIENTS / IDENTITY INFORMATION

Chemical Names	CAS #	SARA Title III SEC 313	ACGIH TLV/TWA	OSHA PEL	% By Wt.
Mineral spirits	64741-65-7	No	177 ppm*	177 ppm*	20-30
Isoparaffinic Solvent	64741-66-8	No	NE	400 ppm**	40-50
Mineral oil	8042-47-5	No	NE	NE	10-20
Propane	68476-85-7	No	2500 ppm	1000 ppm	10-20

\* ExxonMobil recommendation \*\* Exxon recommendation  
 Balance of ingredients are non-hazardous or below reportable levels.

SECTION III - PHYSICAL CHARACTERISTICS

Boiling Point: NA Vapor Pressure (psig): 60@130F Specific Gravity (H2O=1): <1.0  
 Solubility/Water: Negligible Vapor Density (AIR=1): >1 Evaporation Rate (Ether=1): <1  
 Appearance and Odor: Clear with Hydrocarbon Odor

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

Aerosol Flammability: Product is to be labeled as flammable as described in 16 CFR 1500.3 and 1500.45.  
 Flashpoint: <0F (Propellant); >80F (Concentrate)  
 Flammable Limits - % Volume In Air (Propellant): LEL: 2.2 UEL: 9.5  
 Extinguishing Media: Carbon dioxide, foam and/or dry chemical may be used.  
 Special Fire Fighting Procedures: Containers should be cooled with water to prevent vapor pressure build up.  
 Use equipment or shielding, as required, to protect personnel from bursting, rupturing or venting containers.  
 Unusual Fire and Explosion Hazards: At elevated temperatures:(over 54C-130F) containers exposed to direct flame or heat contact should be cooled with water to prevent weakening of container structure.

SECTION V - REACTIVITY DATA

Stability: Stable Hazardous Polymerization: NA  
 Incompatibility (Materials to Avoid): Oxidizing agents Hazardous Decomposition Products:  
 Carbon Monoxide, Carbon Dioxide and additional hazardous chemicals may be formed in small amounts.  
 Conditions to Avoid: Do not store above 54C-130F. Keep away from heat, direct sunlight, open flames or sparks. Dropping of containers may cause bursting.