

Stability STABLE  
Materials to Avoid  
BASES AND OXIDIZERS, SOME METALS

Conditions to Avoid  
OVERHEATING OR  
FREEZING CONDITIONS

Incompatibility

Conditions to Avoid  
N/A

Hazardous Polymerization? NO  
Hazardous Decomposition Products  
CARBON MONOXIDE AND CARBON DIOXIDE

=====  
VII. ENVIRONMENTAL PROTECTION PROCEDURES

Spill Response

FLOOR MAY BE SLIPPERY, USE CARE TO AVOID FALLING. CONTAIN SPILL WITH INERT MATERIAL (SAND, EARTH), TRANSFER LIQUIDS AND SOLID MATERIAL TO SEPARATE DISPOSAL CONTAINERS. NEUTRALIZE AREA WITH MILD BASE SOLUTION (SODA ASH OR SODIUM BICARBONATE). RINSE AREA THOROUGHLY WITH WATER TO SEWER.

Waste Disposal Method

AFTER MATERIAL HAS BEEN COLLECTED, DISPOSE OF IN ACCORDANCE WITH ALL LOCAL, STATE AND FEDERAL REGULATIONS.

=====  
VIII. SPECIAL PROTECTION INFORMATION

Eye Protection

SAFETY GLASSES

Respiratory Protection (Specific Type)

NONE NEEDED UNDER NORMAL USAGE

Other Protection

EYE BATH AND SAFETY SHOWER AVAILABLE

PROTECTIVE CLOTHING SHOULD BE WORN TO GUARD AGAINST SPLASHING.

Skin Protection

RUBBER GLOVES

Ventilation Recommended

PROVIDE ADEQUATE VENTILATION

=====  
IX. SPECIAL PRECAUTIONS

Hygienic Practices in Handling & Storage

STORE IN TIGHTLY CLOSED CONTAINERS IN A COOL DRY AREA AWAY FROM INCOMPATIBLE MATERIAL. KEEP FROM OVERHEATING OR FREEZING.

Precautions for Repair & Maintenance of Contaminated Equipment

WASH WITH WATER UNTIL RINSATE IS CLEAR.

Other Precautions

HMIS HAZARD RATING: HEALTH - 1, FLAMMABILITY - 0, REACTIVITY - 0, PPE - B.

HMIS INDEX: 0 - MINIMAL, 1 - SLIGHT, 2 - MODERATE, 3 - SERIOUS, 4 - SEVERE.

Additional Comments

KEEP AWAY FROM CHILDREN AND UNTRAINED PERSONNEL.

CHAMELEON FLOOR PREP PREPARED: JULY 7, 2003 BY M.PRIMEAUX

PRODUCT CODE: 03 CFP  
=====