

procedures: ASTM D-4276 and OSHA (29 CFR 1910.146).

**PROTECT ENVIRONMENT:** Contain liquid to prevent contamination of soil, surface water or ground water. Material is heavier than water and has limited water solubility. It will collect on the lowest surface.

**CLEANUP:** For large spills: Evacuate spill area. Contain liquid; transfer to properly labeled closed metal containers. For small spills: mop or soak up immediately. Place in properly labeled metal containers.

## 7. HANDLING AND STORAGE

**HANDLING:** To avoid uncontrolled emissions vent vapor from container to storage tank. Do not eat, drink, or smoke in working area. Refer to Exposure Controls/Personal Protection, Section 8, of the MSDS. Containers, even those that have been emptied, can contain vapors. Do not cut, drill, grind, weld, or perform similar operations on or near empty containers. Vapors of this product are heavier than air and will collect in low areas such as pits, degreasers, storage tanks, and other confined areas. Do not enter these areas where vapors of this product are suspected unless special breathing apparatus is used and an observer is present for assistance.

**STORAGE:** Keep containers tightly closed when not in use. For more Storage and Handling information refer to bulletin #100-06170. Store in a dry place. Do not store in aluminum, zinc, aluminum alloys and plastics. Product should not be packaged in aluminum aerosol cans or with finely divided aluminum or its alloys in an aerosol can. Product is denser than water. Design storage containers appropriately.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**ENGINEERING CONTROLS:** Provide general and/or local exhaust ventilation to control airborne levels below the exposure guidelines. Lethal concentrations may exist in areas with poor ventilation.

### PERSONAL PROTECTIVE EQUIPMENT

**EYE/FACE PROTECTION:** Use safety glasses. If vapor exposure causes eye discomfort, use a full-face respirator.

**SKIN PROTECTION:** Use protective clothing impervious to this material. Selection of specific items such as face shield, gloves, boots, apron, or full-body suit will depend on operation. Remove contaminated clothing immediately, wash skin area with soap and water, launder clothing before reuse.

**RESPIRATORY PROTECTION:** Atmospheric levels should be maintained below the exposure guideline. When respiratory protection is required, use an approved air-purifying or positive-pressure supplied-air respirator depending on the potential concentration. For emergency and other conditions where the exposure guideline may be greatly exceeded, use an approved positive-pressure self-contained breathing apparatus or positive-pressure airline with auxiliary self-contained air

— DISTRIBUTED BY —  
NATIONAL AMERICAN SALES  
504-447-1434  
800-821-3732 (LA)